



| PIN | COM | PIN | COM | PIN | COM  | PIN | COM  |
|-----|-----|-----|-----|-----|------|-----|------|
| 1   | COM | 11  | 2C  | 21  | 4A   | 31  | 2F   |
| 2   | 1B  | 12  | 3DP | 22  | 4F   | 32  | 2G   |
| 3   | K   | 13  | 3E  | 23  | 4G   | 33  | 1CQL |
| 4   | 1DP | 14  | 3D  | 24  | 3B   | 34  | 1B   |
| 5   | 1E  | 15  | 3C  | 25  | 3A   | 35  | 1A   |
| 6   | 1D  | 16  | 4DP | 26  | 3F   | 36  | 1F   |
| 7   | 1C  | 17  | 4E  | 27  | 3G   | 37  | 1G   |
| 8   | 2DP | 18  | 4D  | 28  | 2CQL | 38  | ←    |
| 9   | 2E  | 19  | 4C  | 29  | 2B   | 39  | □    |
| 10  | 2D  | 20  | 4B  | 30  | 2A   | 40  | COM  |

DISPLAY TYPE: TN/POSITIVE  
 VIEWING DIRECTION: 600  
 DISPLAY MODE 1 : REFLECTIVE  
 DISPLAY MODE 2 : TRANSFLECTIVE  
 DRIVING METHOD: STATIC  
 OPERATING VOLTAGE: 5.0V  
 OPERATING TEMPERATURE: -30~85°C  
 STORAGE TEMPERATURE: -30~85°C  
 CONNECTOR: PIN